

**Direct Colors Inc.  
Krystal Kote  
Technical Data**

Product Description		Single component, 100% acrylic floor sealer that exhibits excellent characteristics for abrasion, flexibility, adhesion, chemical resistance, weathering, and UV stability.	
Appearance		Clear gloss	
Recommended for:		Residential and commercial, interior and exterior surfaces; decks, driveways, patios, pavers, and all deck coat overlays	
Application Method		Can be applied by roller, brush, sprayer, lambs wool applicator, pump-up sprayer , high pressure sprayer (pump-up sprayer should be used only when coating a porous surface).	
Typical Properties	3 Coverage Total Solids % VOC Shelf life Ph Viscosity Finish characteristics 12-13 months exposure Application temp	150 to 300 sq ft per gallon 45% 89 grams per liter (.7427 lbs per gallon) 1 year + 8.0 – 9.0 500 cps high gloss, 77 at 60 degrees (Erichsen glossmeter) In progress Above 50°F	
Chemical Resistance	Water Formula 409 Gasoline Brake Fluid Transmission Fluid MEK Xylene Methyl Alcohol 20% Nitric acid 50% Sodium Hydroxide Resistance Properties (hot tire test)	Rating 10 9 4 6 10 3 7 9 9 10 10	Rating Key Contact was maintained for 30 minutes; 10 is best down to 1
Surface Preparation		Surface to be coated should be clean and dry.	
Re-coat or top coating		Multiple coats of this product are acceptable. If you opt to recoat this product, you must allow the first coat to dry (to touch).	

Krystal Kote Tech Specs

Product Storage	Short-term: (Immediately prior to use) 40°F to site temp Continuous storage should be above 40°F
Clean up	Soap and water
Safety	Material Safety Data Sheets are available upon request from Direct Colors Inc.. This product is intended for use by both professionals and amateurs. Keep away from children.
Important Notice	These products are sold subject only to the express warranties contained herein. There are no other warranties by Direct Colors Inc. of any nature whatsoever expressed or implied. Including any warranties of merchantability or fitness for a particular purpose in connection with this product. Buyer agrees that seller assumes no liability for remote or consequential damages of any kind which result from the used or misuse of the product. Information contained herein is based on data believed to be reliable; however, it is the buyer's responsibility to satisfy itself of the product for a particular purpose.