

EASYREPAIR™

TECHNICAL DATA SHEET



DESCRIPTION

EasyRepair™, a specialized maintenance and correction solution, is designed to restore and blend imperfections in existing EasySeal™ solvent-based acrylic coatings. Its reflowing solvent action re-casts the coating surface to eliminate bubbles, streaks, and gloss inconsistencies. EasyRepair™ revives the clarity and uniformity of sealed concrete finishes—delivering a flawless, professional-grade result without the need for full resealing.

EasyRepair™ should be applied only to surfaces previously sealed with a solvent-based acrylic coating such as EasySeal™ or EasyTint™. This product is formulated to rejuvenate small, localized areas—typically under 50 sq ft—where over-application, bubbling, or surface haze has occurred.

It works by gently re-dissolving the sealer film and allowing it to re-level into a smooth, uniform finish.

Do not apply over polyurethane, epoxy, or any water-based sealer (e.g., AcquaSeal™ or AcquaTint™).

PRODUCT BENEFITS

- Re-casts existing solvent-based acrylic sealer films for a smooth, uniform appearance
- Corrects bubbles, streaks, and haze without stripping or full reapplication
- Reduces the need for labor-intensive mechanical or chemical removal
- Extends the service life of the existing sealer
- Easy, targeted application—ideal for maintenance and small-area touch-ups
- Fast-acting solvent system ensures efficient repair and consistent blending

APPLICATION

- Tools: Use a foam brush or short-nap solvent-resistant roller for best control.
- Application: Apply a thin, even coat over the affected area.
- Technique: Use overlapping strokes to reflow and blend imperfections. Avoid puddling or oversaturation.
- Multiple Treatments: For heavily over-applied or rough areas, a second light application may be needed after full drying.
- Dry Time: Allow 48–72 hours before sealing, waxing, or exposing to foot traffic.
- Cleanup: Clean tools immediately with xylene or a comparable solvent.

COVERAGE

Estimated coverage is approximately 200 sq ft (18.58 m²) per gallon.

Actual coverage may vary based on surface porosity, texture, and defect severity.

LIMITATIONS & PRECAUTIONS

- For solvent-based acrylic sealers only.
- Not suitable for polyurethane, epoxy, or water-based coatings.
- Avoid application in enclosed spaces without adequate ventilation.
- Do not smoke or use near heat, sparks, or open flame.
- Overuse or application to large areas may cause uneven sheen or soft film.

CLEAN UP

For immediate cleanup of spills or tools before drying, use xylene or a comparable solvent.

Do not thin EasyRepair™ prior to use.

If cured product removal is necessary, employ mechanical methods such as light sanding or solvent stripping with caution.

DISPOSAL

For the disposal of any unused product, please refer to your local environmental or hazardous waste management authority to ensure compliance with local regulations.

SHELF LIFE AND STORAGE

This product should be used within one year of purchase for optimal effectiveness. For storage, keep the product indoors, in a cool area away from direct sunlight and heat sources.

TECHNICAL SERVICE & SUPPORT

Direct Colors offers comprehensive technical assistance and consulting services. Our expertise includes product selection guidance, specification details, troubleshooting support, and advice on the effective repair and protection of concrete surfaces. We are committed to providing tailored solutions to meet your specific project needs.

WARRANTY

EasyRepair™, a proprietary product, is guaranteed to maintain uniform quality within the bounds of manufacturing tolerances. However, as we have no control over its application, no explicit or implied warranty is provided concerning the effects of such use. In the event of a proven defect, our liability is strictly limited to refunding the purchase price of the defective material. The user is responsible for all other risks and liabilities that may arise from the use of this product. For any inquiries, please reach out to Direct Colors customer service.

HEALTH & SAFETY GUIDELINES

DANGER: FLAMMABLE LIQUID AND VAPOR. HARMFUL OR FATAL IF SWALLOWED.
Use only with adequate ventilation. Avoid inhalation or skin contact. Keep away from ignition sources.
Contains: Xylene, petroleum distillates, trimethylbenzene derivatives.
FIRST AID:
If swallowed—call a physician immediately. Do not induce vomiting.
If in eyes—flush with water 15 minutes. If on skin—wash thoroughly with soap and water.
If inhaled—move person to fresh air.
WARNING: This product can expose you to chemicals including Ethylbenzene and Toluene known to cause cancer and reproductive harm. Visit www.P65Warnings.ca.gov

.

TECHNICAL DATA

Physical State	Liquid
Color	Clear
Odor	Solvent
Solubility in Water	N/A
VOC	< 83%
Specific Gravity	~ 0.919
Flash Point	92.9°F (38.87°C)